Form 282 – Asphalt Paving Inspector's Daily Report Completion Instructions

Form 282 may be used to document daily asphalt paving operations. Its use is optional in lieu of other acceptable recording methods, as determined by the Project Engineer, to record loads delivered, location placed, spread yield, and asphalt temperatures. Complete Form 282 as follows:

- 1. Weather, Air Temperature, and Date. Enter the date and enter the weather conditions and maximum and minimum air temperatures for that date.
- 2. Project No. and Project Code (SA#). Fill in as appropriate.
- 3. Load No. Record the load number from the Contractor's load ticket. The load number will indicate the sequential loading order from the plant. If a load arrives to the project site out of sequence according to the load number, the truck may have been substantially delayed and the Hot Bituminous Pavement temperature should be checked against allowable minimum temperature, as per specification.
- 4. Ticket No. Enter the ticket number from the Contractor's load ticket for each load delivered to the project.
- 5. Ticket Weight. Enter the net weight (tons) from the load ticket of each load.
- 6. Cumulative Weight. Enter the cumulative weight of asphalt by adding the net weight for each ticket to the previous cumulative total.
- 7. Station to Station. Record the beginning and ending station of the placement location for each load of asphalt.
- 8. Location. Enter the lane and direction being paved.
- 9. Paver Pass. Record the thickness (inches) and width (feet) of asphalt being placed.

B-57

- 10. Course. Check the appropriate box for bottom or top lift.
- 11. Spread Yield. Any method to calculate spread yield is acceptable as long as the calculation results in an accurate comparison between the actual application rate and the plan application rate.

The following method provides a relative comparison of actual-to-plan application rates. A calculated result over 1.00 indicates that the actual application rate is exceeding the plan application rate. For example, a spread yield rate of 1.05 indicates that the plan quality is being overrun by five percent for the asphalt quantity placed.

First determine the correct plan application rate factor as follows:

$$2,000 \times 9$$

Plan Application Rate (pounds/square yard/inch)

The plan application rate can be found in the General Notes of the plans. In this example, use 112 pounds/square yard/inch.

Factor =
$$\frac{2,000 \times 9}{112}$$
 = 160.7

Calculations can be completed for a single load, any portion of the day, or the entire day's run as follows:

 $Factor \times Actual \ Tons/Thickness/Width/Station - Station \ Length$

A. Single Load: $160.7 \times 12.88/2/12.5/75 = 1.10$

B. Partial Day: $160.7 \times (109.04 - 26.83)/2/12.5/(52,680 - 52,160) = 1.02$

C. Entire Day: $160.7 \times 146.1/2/12.5/(52,915 - 52,000) = 1.03$

12. Mix Temp. Record the delivered mix temperature.

B-58

- 13. Remarks. Provide any appropriate remarks.
- 14. Signed and Title. The Form 282 needs to be signed by the person who completed the form.

. B-59

Newther Newt	ASP	ASPHALT PAVING INSPECTOR DAILY REPORT	INING I	NSPECT	TOR DA	ILY REF	ORT				:	!		
Minimum: 72° © Sanger No: Course Springle No	Weather: Clear, Wa	līm.			Ð	_	Date: 9/1/95				Proje 1111	ct Code (SA#)	@	
Countedfive Station to Station Location Paver Pass Course Spread Spring Weight Weight Weight Station to Station Location This. Width Bot. Top Year 12.86 S20+075 SEL Lane 2" 12.5 V	Air Temp	erature: Maximum: 80°		Minimum: 72°	0		Project No.: Sampte							497
12.86 12.86 520+00 520+75 581 Lane 2" 12.5 V M 13.85 26.83 520+75 521+60 581 Lane 2" 12.5 V M 22.02 63.99 522+65 524+00 581 Lane 2" 12.5 V M 22.03 526+60 527+70 581 Lane 2" 12.5 V M 22.03 108.04 522+45 584 Lane 2" 12.5 V M 22.03 108.04 522+45 584 Lane 2" 12.5 V M 22.03 108.04 527+70 529+15 581 Lane 2" 12.5 V M 22.03 146.10 527+70 529+15 581 Lane 2" 12.5 V M 22.03 146.10 527+70 529+15 581 Lane 2" 12.5 V M 22.03 146.10 527+70 529+15 581 Lane 2" 12.5 V M 22.03 146.10 527+70 529+15 581 Lane 2" 12.5 V M 22.03 146.10 527+70 529+15 581 Lane 2" 12.5 V M 22.03 146.10 527+70 529+15 581 Lane 2" 12.5 V M 22.03 146.10 527+70 529+15 581 Lane 2" 12.5 V M 22.03 146.10 527+70 529+15 581 Lane 2" 12.5 V M 22.03 146.10 527+70 529+15 581 Lane 2" 12.5 V M 22.04 146.10 527+70 146.10 529+15 146.10	Load No.	Ticket No.		Cumulative Weight	Station t	o Station	Location		r Pass	Bot.	Top	Spread Yield	Mix Temp,	Remarks
13.96 26.83 520+75 521+60 SB Lane 2° 12.5 V 22.02 66.39 522+55 SB Lane 2° 12.5 V 22.13 106.04 525+45 SB Lane 2° 12.5 V 22.13 106.04 525+45 SB Lane 2° 12.5 V 22.13 106.04 525+45 SB Lane 2° 12.5 V 22.73 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.73 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.73 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.74 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.75 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.75 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.75 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.75 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.75 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.75 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.75 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.77 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.78 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.79 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.71 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.72 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.73 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.74 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.75 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.77 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.78 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.79 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.71 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.72 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.73 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.74 146.10 527+70 529+15 SB Lane 2° 12.5 V 22.75 146.10 0.00 0.00 0.00 0.00 0.00 0.00 0.00	-	8680	12.88		520+00	520+75	SB Lane	'n	12.5		>		255°	North Approach
14.14 40.97 521+60 522+65 SB Lane 2° 12.5 V (6) 22.92 66.91 522+65 SB Lane 2° 12.5 V (6) 22.13 106.04 525+45 SB Lane 2° 12.5 V (7) 22.13 106.04 525+45 SB Lane 2° 12.5 V (7) 22.73 146.10 527+70 SB Lane 2° 12.5 V (7) 22.73 146.10 527+70 SB Lane 2° 12.5 V (7) 22.73 146.10 527+70 SB Lane 2° 12.5 V (7) 22.73 146.10 527+70 SB Lane 2° 12.5 V (7) 22.73 146.10 527+70 SB Lane 2° 12.5 V (7) 22.73 146.10 527+70 SB Lane 2° 12.5 V (7) 22.73 146.10 527+70 SB Lane 2° 12.5 V (7) 22.73 146.10 527+70 SB Lane 2° 12.5 V (7) 22.73 146.10 527+70 SB Lane 2° 12.5 V (7) 22.73 146.10 527+70 SB Lane 2° 12.5 V (7) 22.73 146.10 527+70 SB Lane 2° 12.5 V (7) 22.73 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.73 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.73 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.73 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.73 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.73 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.73 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.73 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.73 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.73 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.73 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.74 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.74 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.74 146.10 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.75 140.00 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.75 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.75 140.00 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.75 140.00 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.75 140.00 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.75 140.00 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.75 140.00 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.75 140.00 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.75 140.00 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.75 140.00 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.75 140.00 SZ 140.00 SZ 140.00 SB Lane 2° 12.5 V (7) 22.75 140.00 SZ 140.00 SZ 140.00 SB Lane 2° 12	2	8681	13.95		520+75	521+60	SB Lane	2.	12.5		>)	260°	To Str. F-15-CP
23.02 63.39 522+55 524+00 SB Lane 2° 12.5	m	8683	14.14		521+60	522+55	SB Lane	2	12.5		7		265°	
22.73 108.04 525.45 58 Lane 2° 12.5 V 22.73 108.04 525.45 526+80 58 Lane 2° 12.5 V 22.73 146.10 527.70 529+15 58 Lane 2° 12.5 V 22.73 146.10 527.70 529+15 58 Lane 2° 12.5 V (I) (I) (I) (II) (II) (II) (II) (II) (4	8685	23.02		522+55	524+00	SB Lane	2	12.5		>	Ι.	260°	
22.73 108.04 \$25445 \$26480 \$81 Lane 2° 12.5 V 22.73 146.10 \$27470 \$82 Lane 2° 12.5 V 22.73 146.10 \$27470 \$629+15 \$81 Lane 2° 12.5 V (6) (7) (10) (10) (10) (10) (10) (10) (10) (10	3	9898	22.92	96.91	524+00	525+45	SB Lane	2	12.5		7			
14.00 123.37 526+80 527+70 SB Lane 2° 12.5 V 22.73 146.10 527+70 529+15 SB Lane 2° 12.5 V (D)	9	8682	22.13		525+45	526+80	SB Lane	5*	12.5		>		250°	
22.73 146.10 527+70 529+15 SB Lane 2° 12.5 V © (I) (II) (II) (II) (II) (II) (II) (II	7	1898	14.00		526+80	527+70	SB Lane	2*	12.5		7			
(6) (7) (10) (10) (10) (10) (10) (10) (10) (10	89	8898	22.73		527+70	529+15	SB Lane	2=	12.5		7	(260°	
(i) (ii) (iii) (iii) (iii) (iii) (iii) (iii) (iii) (iii) (iii) (iiii) (iiii) (iiiiiiii												I —		<== Overhaul Yield (SB)
s used were inspected and found to conform reasonably with the Contract	(ı		(Ľ		,	_		(1	1	((
i used were inspected and found to conform reasonably with the Contract s noted.	<u>(6)</u>	Ð	(3)	9		1	8	נצ		(0)	9		(12)	(13)
i used were inspected and found to conform reasonably with the Contract)									})
s used were inspected and found to conform reasonably with the Contract														
s used were inspected and found to conform reasonably with the Contract														
s used were inspected and found to conform reasonably with the Contract s noted.														
s used were inspected and found to conform reasonably with the Contract s noted.														-
s used were inspected and found to conform reasonably with the Contract s noted.														
s used were inspected and found to conform reasonably with the Contract s noted.														
s used were inspected and found to conform reasonably with the Contract s noted.														
s used were inspected and found to conform reasonably with the Contract s noted.														
s used were inspected and found to conform reasonably with the Contract s noted.														
s used were inspected and found to conform reasonably with the Contract s noted.														
s used were inspected and found to conform reasonably with the Contract s noted.														
s used were inspected and found to conform reasonably with the Contract s noted.														
s noted.	This ite.	and the ma	Itariale Incod	you inches	and but for	not to confor	n reasonah	h with th	Contra	\ \frac{1}{2}	Signed:	1 Set	(3	
	Plans a	nd Specificati	ions as note	j.							Title: 6			
	Distribution	in: Project File (o	original)											CDOT Form 282 07/02

. B-60